



2608

AC A	6/15/60/150/300A $\pm 3\%$ of FS
AC V	150/300/600V $\pm 3\%$ of FS
DC V	60V $\pm 3\%$ of FS
Ω	1/10k Ω (25/250 Ω mid-scale) $\pm 2\%$ of scale length
Temperature	-20 $^{\circ}$ C~+150 $^{\circ}$ C (with the use of Temperature Probe 7060) $\pm 5^{\circ}$ C (0 $^{\circ}$ C~+100 $^{\circ}$ C) $\pm 10^{\circ}$ C (other ranges)
Conductor Size	$\varnothing 33$ mm max.
Frequency Response	50Hz/60Hz
Safety Standard	IEC 61010-1 CAT.III 300V Pollution Degree 2 IEC 61010-2-031 IEC 61010-2-032
Withstand Voltage	3700V AC for 1 minute
Power Source	R6P (AA) (1.5V) $\times 1$
Dimensions	193(L) \times 78(W) \times 39(D)mm
Weight	275g approx.
	7066A (Test leads) 8923 (Fuse [0.5A/600V]) $\times 2$ 9097 (Carrying case) R6P (AA) $\times 1$ Instruction Manual
Optional	7060 (Temperature probe) 8008 (Multi-Tran)